

Package: posteriordb (via r-universe)

September 19, 2025

Type Package

Title R Functionality for PosteriorDB

Version 0.3.4

Date 2025-08-12

Maintainer Mans Magnusson <mans.magnusson@gmail.com>

Description R functionality of easy handling of the posteriordb posteriors.

License BSD_3_clause + file LICENSE

RoxygenNote 7.3.1

Encoding UTF-8

Depends R (>= 3.5.0)

Imports checkmate, gh, jsonlite

Suggests bibtex, BH, covr, digest, dplyr, dotenv, httr, git2r, posterior, remotes, rmarkdown, rstan, RcppEigen, testthat, tibble, yaml, knitr

VignetteBuilder knitr

Config/pak/sysreqs git libssl-dev

Repository <https://r-multiverse.r-universe.dev>

Date/Publication 2025-08-12 08:56:59 UTC

RemoteUrl <https://github.com/stan-dev/posteriordb-r>

RemoteRef v0.3.4

RemoteSha dfd1de915900e77affa65ed1da2149a211a54b5b

Contents

alias_names	3
as.data.frame.pdb_posterior	3
as.reference_posterior_draws.stanfit	4
assert_checked_reference_posterior_draws	5
bibliography	6

check_pdb	6
check_pdb_posterior	7
check_reference_posterior_draws	8
check_summary_statistics_draws	9
compute_reference_posterior_draws	9
compute_reference_posterior_draws_stan_sampling	10
compute_reference_posterior_summary_statistic	10
data_file_path	11
data_info	11
data_names	12
filter_posteriors	13
framework	13
get_data	14
github_pat	15
handle_aliases	15
info	15
info<-	16
model_code	16
model_names	17
pdb<-	18
pdb_aliases	18
pdb_assert_file_exist	19
pdb_cached_local_file_path	19
pdb_cache_path	20
pdb_cache_rm	20
pdb_compare_stan_models	21
pdb_file_copy	21
pdb_local	22
pdb_stan_sampling_versions	23
pdb_version	24
posterior	24
posteriors_tbl_df	25
posterior_dimension_names	26
posterior_names	26
read_json_from_pdb	27
reference_posterior_draws_file_path	27
reference_posterior_info	28
reference_posterior_names	29
reference_posterior_summary_statistic	29
remove_pdb	30
rename_pdb	31
run_stan	32
subset.pdb_reference_posterior_draws	32
summary_statistic_type	33
thin_draws.pdb_reference_posterior_draws	33
write_pdb	34

alias_names	<i>Get all existing alias names from a posterior database</i>
-------------	---

Description

Get all existing alias names from a posterior database

Usage

```
alias_names(type, pdb = pdb_default())
```

Arguments

type	type of alias names. Cureently only posteriors.
pdb	a pdb object.

as.data.frame.pdb_posterior	<i>Coerce a [pdb_posterior] to a Data Frame</i>
-----------------------------	---

Description

Coerce a [pdb_posterior] to a Data Frame

Usage

```
## S3 method for class 'pdb_posterior'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)

## S3 method for class 'pdb_posteriors'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

x	a [pdb_posterior] object.
row.names	NULL or a character vector giving the row names for the data frame. Missing values are not allowed.
optional	Not used.
...	further arguments to as.data.frame for a list.

Details

The dataframe will consist of one row per keyword.

`as.reference_posterior_draws.stanfit`*Reference Posterior draws and summary statistics*

Description

Reference Posterior draws and summary statistics

Usage

```
## S3 method for class 'stanfit'
as.reference_posterior_draws(x, info, pdb = pdb_default(), ...)

reference_posterior_draws(x, ...)

as.reference_posterior_draws(x, ...)

pdb_reference_posterior_draws(x, ...)

as.pdb_reference_posterior_draws(x, ...)

## S3 method for class 'character'
reference_posterior_draws(x, pdb = pdb_default(), ...)

## S3 method for class 'pdb_posterior'
reference_posterior_draws(x, ...)

## S3 method for class 'pdb_reference_posterior_info'
reference_posterior_draws(x, pdb = pdb_default(), ...)

## S3 method for class 'draws_list'
as.reference_posterior_draws(x, info, ...)

assert_reference_posterior_draws(x)
```

Arguments

<code>x</code>	a [posterior] object or a posterior name.
<code>info</code>	a [pdb_reference_posterior_info] object
<code>pdb</code>	a [pdb] object (if [x] is a posterior name)
<code>...</code>	further arguments supplied to specific methods.

Value

a [pdb_reference_posterior] object.

`assert_checked_reference_posterior_draws`*Assert that all checks of the reference posterior draws are true*

Description

Assert that all checks of the reference posterior draws are true

Usage

```
assert_checked_reference_posterior_draws(x)

## S3 method for class 'pdb_reference_posterior_draws'
assert_checked_reference_posterior_draws(x)

## S3 method for class 'pdb_reference_posterior_info'
assert_checked_reference_posterior_draws(x)

assert_checked_summary_statistics_draws(x)

## S3 method for class 'pdb_reference_posterior_draws'
assert_checked_summary_statistics_draws(x)

## S3 method for class 'pdb_reference_posterior_summary_statistic'
assert_checked_summary_statistics_draws(x)

## S3 method for class 'pdb_reference_posterior_info'
assert_checked_summary_statistics_draws(x)
```

Arguments

x a [pdb_reference_posterior_draws] object

Details

This function asserts that the reference posterior draws comply with the criterias of the reference posterior draws.

See https://github.com/stan-dev/posteriordb/blob/master/doc/REFERENCE_POSTERIOR_DEFINITION.md for details.

bibliography	<i>Get the bibliography of a posterior database</i>
--------------	---

Description

Get the bibliography of a posterior database

Usage

```
bibliography(pdb, ...)
```

```
pdb_bibliography(pdb, ...)
```

Arguments

pdb	a posterior database connection
...	further arguments passed to [bibtex::read.bib]

check_pdb	<i>Check the content a posterior database</i>
-----------	---

Description

Check the content a posterior database

Usage

```
check_pdb(
  pdb,
  posterior_names_to_check = NULL,
  run_stan_code_checks = FALSE,
  verbose = TRUE
)

check_pdb_read_model_code(posterior_list)

check_pdb_aliases(pdb)

check_pdb_read_data(posterior_list)

check_pdb_read_reference_posterior_draws(posterior_list)

check_pdb_posterior_run_stan(po)

check_pdb_references(pdb)
```

```

check_pdb_posterior_references(posterior_list)

check_pdb_all_models_have_posterior(pdb)

check_pdb_all_data_have_posterior(pdb)

check_pdb_all_reference_posteriors_have_posterior(pdb)

```

Arguments

pdb a pdb object
posterior_names_to_check an vector indicating what posteriors to check in the pdb. Default is NULL (all).
run_stan_code_checks should checks using Stan be run?
verbose should check results be printed?
posterior_list a list of pdb_posterior objects.
po a pdb_posterior object.

Details

[check_pdb()] checks that the content exists as specified [check_pdb_run_stan()] test to run all posteriors with stan models. [check_pdb_stan_syntax()] check that all stan model code files can be parsed. [check_pdb_aliases()] check that all alias are correct. [check_pdb_read_model_code()] check that posteriors can be read. [check_pdb_posteriors()] check a vector of posterior names. [check_pdb_references()] check that all references in posteriors also exist in bibtex. [check_pdb_all_models_have_posterior()] check that all models belong to a posterior [check_pdb_all_data_have_posterior()] check that all datasets belong to a posterior [check_pdb_all_reference_posteriors_have_posterior()] check that all reference posteriors belong to a posterior

Value

a boolean indicating if the pdb works as it should.

check_pdb_posterior	<i>Test a posterior</i>
---------------------	-------------------------

Description

Test a posterior

Usage

```
check_pdb_posterior(po, run_stan_code_checks = TRUE, verbose = TRUE)
```

Arguments

po a [pdb_posterior] to check.

run_stan_code_checks should checks using Stan be run?

verbose should check results be printed?

Details

The function checks that a posterior is consistent.

check_reference_posterior_draws

Check that reference posterior draws follows the reference posterior draws definition.

Description

Check that reference posterior draws follows the reference posterior draws definition.

Usage

```
check_reference_posterior_draws(x, ...)

## S3 method for class 'character'
check_reference_posterior_draws(x, ...)

## S3 method for class 'pdb_posterior'
check_reference_posterior_draws(x, ...)

## S3 method for class 'pdb_reference_posterior_draws'
check_reference_posterior_draws(x, ...)
```

Arguments

x a posterior name, posterior object or reference_posterior_draws object

... currently not used.

```
check_summary_statistics_draws
```

Check that reference posterior draws follows the reference posterior summary definition.

Description

Check that reference posterior draws follows the reference posterior summary definition.

Usage

```
check_summary_statistics_draws(x, ...)

## S3 method for class 'character'
check_summary_statistics_draws(x, ...)

## S3 method for class 'pdb_posterior'
check_summary_statistics_draws(x, ...)

## S3 method for class 'pdb_reference_posterior_draws'
check_summary_statistics_draws(x, ...)
```

Arguments

x	a posterior name, posterior object or reference_posterior_draws object
...	currently not used.

```
compute_reference_posterior_draws
```

Compute a Reference Posteriors for a reference posterior info object

Description

Compute a Reference Posteriors for a reference posterior info object

Usage

```
compute_reference_posterior_draws(rpi, pdb = pdb_default())
```

Arguments

rpi	a [reference_posterior_info] object.
pdb	a [pdb] object.

```
compute_reference_posterior_draws_stan_sampling
```

Compute a Reference Posteriors using Rstan

Description

Compute a Reference Posteriors using Rstan

Usage

```
compute_reference_posterior_draws_stan_sampling(rpi, pdb)
```

Arguments

`rpi` a [reference_posterior_info] object.
`pdb` a [pdb] object.

```
compute_reference_posterior_summary_statistic
```

Compute Summary statistics from a reference posterior

Description

Compute Summary statistics from a reference posterior

Usage

```
compute_reference_posterior_summary_statistic(rpd, summary_statistic = "mean")  
  
compute_summary_statistic(rpd, summary_statistic = "mean")
```

Arguments

`rpd` a [reference_posterior_summary_statistic] object
`summary_statistic`
summary statistic to compute

data_file_path	<i>Extract data for posterior</i>
----------------	-----------------------------------

Description

Extract data for posterior

Usage

```
data_file_path(x, ...)
stan_data_file_path(x, ...)
stan_data(x)
```

Arguments

x	an object to access file path to.
...	further arguments supplied to methods.

data_info	<i>Access data and model information</i>
-----------	--

Description

Access data and model information

Usage

```
data_info(x, ...)
as.data_info(x, ...)

## S3 method for class 'pdb_posterior'
data_info(x, ...)

## S3 method for class 'character'
data_info(x, pdb = pdb_default(), ...)

## S3 method for class 'list'
as.data_info(x, pdb = NULL, ...)

pdb_data_info(x, ...)
as.pdb_data_info(x, ...)
```

```

model_info(x, ...)

as.model_info(x, ...)

pdb_model_info(x, ...)

as.pdb_model_info(x, ...)

## S3 method for class 'pdb_posterior'
model_info(x, ...)

## S3 method for class 'character'
model_info(x, pdb = pdb_default(), ...)

## S3 method for class 'list'
as.model_info(x, pdb = NULL, ...)

```

Arguments

x	a object to access information for.
...	further arguments to methods.
pdb	a pdb object.

data_names	<i>Get all existing data names from a posterior database</i>
------------	--

Description

Get all existing data names from a posterior database

Usage

```

data_names(pdb = pdb_default(), ...)

## S3 method for class 'pdb_local'
data_names(pdb = pdb_default(), ...)

## S3 method for class 'pdb_github'
data_names(pdb, ...)

## S3 method for class 'pdb_github'
model_names(pdb, ...)

## S3 method for class 'pdb_github'
reference_posterior_names(pdb, ...)

```

Arguments

`pdb` a `pdb` object.
`...` Further argument to methods.

<code>filter_posteriors</code>	<i>Filter Posteriors in Database</i>
--------------------------------	--------------------------------------

Description

Filter Posteriors in Database

Usage

```
filter_posteriors(pdb = pdb_default(), ...)
```

Arguments

`pdb` a `pdb` object.
`...` further arguments to supply to `dplyr::filter()`

Details

Filter posteriors in the database and return list of posteriors/models/data to work with as a list.

The function is built upon the `dplyr` filter function and follows the exact same syntax. All elements in the ‘posteriors/[posterior_name].json’, ‘models/info/[model_name].json’ and ‘data/info/[data_name].json’ can be used to filter the posterior database. See examples below.

<code>framework</code>	<i>Identify the framework for a given [model_code]</i>
------------------------	--

Description

Identify the framework for a given [model_code]

Usage

```

framework(x)

## S3 method for class 'pdb_model_code'
framework(x)

framework(x) <- value

## S3 replacement method for class 'character'
```

```
framework(x) <- value

## S3 replacement method for class 'pdb_model_code'
framework(x) <- value
```

Arguments

`x` a [pdb_model_code] object.
`value` a supported framework.

get_data

Posterior Data Sets

Description

Posterior Data Sets

Usage

```
get_data(x, ...)

as.pdb_data(x, ...)

## S3 method for class 'pdb_posterior'
get_data(x, ...)

## S3 method for class 'character'
get_data(x, pdb = pdb_default(), ...)

## S3 method for class 'pdb_data_info'
get_data(x, pdb = pdb_default(), ...)

## S3 method for class 'list'
as.pdb_data(x, info, ...)

pdb_data(x, ...)
```

Arguments

`x` an object to access data from.
`...` Currently not used.
`pdb` a pdb object.
`info` a pdb_data_info object.

github_pat	<i>Retrieve Github personal access token.</i>
------------	---

Description

A github personal access token Looks in env var ‘GITHUB_PAT‘

Usage

```
github_pat(pdb = NULL)
```

Arguments

pdb	A posterior database object to extract pat from.
-----	--

handle_aliases	<i>Return the name that the alias points to</i>
----------------	---

Description

Return the name that the alias points to

Usage

```
handle_aliases(x, type, pdb)
```

Arguments

x	a name to lookup in alias list
type	type of alias names. Cureently only posteriors.
pdb	a pdb object.

info	<i>Extract information from a pdb object</i>
------	--

Description

Extract information from a pdb object

Usage

```
info(x)
```

Arguments

x	a [pdb_data], [pdb_model_code] and [pdb_reference_posterior]
info	a [pdb_]

info<-	<i>Set information to a pdb object</i>
--------	--

Description

Set information to a pdb object

Usage

```
info(x) <- value
```

Arguments

x	a [pdb_data], [pdb_model_code] and [pdb_reference_posterior]
value	an info object

model_code	<i>Extract and construct model code objects</i>
------------	---

Description

Extract and construct model code objects

Usage

```
model_code(x, ...)

as.model_code(x, info, ...)

## S3 method for class 'pdb_posterior'
model_code(x, framework, ...)

## S3 method for class 'character'
model_code(x, framework, pdb = pdb_default(), ...)

## S3 method for class 'pdb_model_info'
model_code(x, framework, pdb = pdb_default(), ...)

## S3 method for class 'stanmodel'
as.model_code(x, info, ...)

## S3 method for class 'character'
as.model_code(x, info, framework, ...)

pdb_model_code(x, ...)
```



```

as.pdb_model_code(x, info, ...)

model_code_file_path(x, ...)

## S3 method for class 'pdb_posterior'
model_code_file_path(x, framework, ...)

## S3 method for class 'pdb_model_info'
model_code_file_path(x, framework, pdb = pdb_default(), ...)

## S3 method for class 'character'
model_code_file_path(x, framework, pdb = pdb_default(), ...)

stan_code_file_path(x)

stan_code(x, ...)

as.stan_code(x, info, ...)

pdb_stan_code(x, ...)

```

Arguments

x	an object to access file path to.
...	further arguments supplied to methods.
info	a <code>pdb_model_info</code> object.
framework	model code framework (e.g. <code>stan</code>).
pdb	a <code>pdb</code> object.

See Also

`framework()`

model_names	<i>Get all existing model names from a posterior database</i>
-------------	---

Description

Get all existing model names from a posterior database

Usage

```

model_names(pdb = pdb_default(), ...)

## S3 method for class 'pdb_local'
model_names(pdb = pdb_default(), ...)

```

Arguments

pdb	a pdb object.
...	Further argument to methods.

pdb<-	<i>Set pdb slot</i>
-------	---------------------

Description

Set pdb slot

Usage

```
pdb(x) <- value
```

Arguments

x	a [pdb_data], [pdb_model_code] and [pdb_reference_posterior]
value	a pdb object

pdb_aliases	<i>Extract aliases list from posterior database</i>
-------------	---

Description

Extract aliases list from posterior database

Usage

```
pdb_aliases(type, pdb)
```

Arguments

type	type of alias names. Cureently only posteriors.
pdb	a pdb object.

`pdb_assert_file_exist` *Assert that a file exists*

Description

Assert that a file exists

Usage

```
pdb_assert_file_exist(pdb, path, ...)
```

```
## S3 method for class 'pdb_local'  
pdb_assert_file_exist(pdb, path, ...)
```

Arguments

<code>pdb</code>	a pdb object.
<code>path</code>	a pdb path.
<code>...</code>	further arguments supplied to methods.

`pdb_cached_local_file_path`
Read json file from path

Description

Read json file from path

Usage

```
pdb_cached_local_file_path(pdb, path, unzip = FALSE)
```

Arguments

<code>pdb</code>	a pdb to read from.
<code>path</code>	a pdb to read from.
<code>unzip</code>	if true, path is zipped and should be unzipped to cache.

Details

Copies the file to the cache and return path

pdb_cache_path	<i>Returns a writable cache path for a pdb and a path It will create the directory if it does not exist.</i>
----------------	--

Description

Returns a writable cache path for a pdb and a path It will create the directory if it does not exist.

Usage

```
pdb_cache_path(pdb, path)
```

Arguments

pdb	a pdb object.
path	a pdb path.

pdb_cache_rm	<i>Remove object from cache</i>
--------------	---------------------------------

Description

Remove object from cache

Usage

```
pdb_cache_rm(x, ...)

## S3 method for class 'pdb_reference_posterior_draws'
pdb_cache_rm(x, ...)

## S3 method for class 'pdb_data'
pdb_cache_rm(x, ...)
```

Arguments

x	an object to remove from cache
...	Currently not in use.

`pdb_compare_stan_models`

Compare two stan models for the same data

Description

Compare two stan models for the same data

Usage

```
pdb_compare_stan_models(po, new_stan_model_code_file, upar_values = NULL)
```

Arguments

<code>po</code>	a 'pdb_posterior' object
<code>new_stan_model_code_file</code>	a file path to another stan code to compare with
<code>upar_values</code>	a list of values on the constrained space to use for comparisons. Defaults to 100 samples from a standard normal.

`pdb_file_copy`

Copy a file from a pdb to a local path

Description

Copy a file from a pdb to a local path

Usage

```
pdb_file_copy(pdb, from, to, overwrite = FALSE, ...)
```

```
## S3 method for class 'pdb_local'
```

```
pdb_file_copy(pdb, from, to, overwrite = FALSE, ...)
```

```
## S3 method for class 'pdb_github'
```

```
pdb_file_copy(pdb, from, to, overwrite = FALSE, ...)
```

Arguments

<code>pdb</code>	a pdb connection.
<code>from</code>	a path in the pdb
<code>to</code>	a local file path
<code>overwrite</code>	overwrite local file.
<code>...</code>	further argument supplied to methods

Value

a boolean indicator as file.copy indicating success.

pdb_local	<i>Create a Posterior Database (pdb) connection</i>
-----------	---

Description

Create a Posterior Database (pdb) connection

Usage

```

pdb_local(
  path = getOption("pdb_path", Sys.getenv("PDB_PATH")),
  cache_path = tempdir()
)

pdb(x, ...)

## Default S3 method:
pdb(x, ...)

## S3 method for class 'pdb_model_code'
pdb(x, ...)

## S3 method for class 'character'
pdb(x, pdb_type = "local", cache_path = tempdir(), ...)

pdb_default(cache_path = tempdir())

pdb_config(directory = getwd())

pdb_github(
  repo = getOption("pdb_repo", "stan-dev/posteriorfdb"),
  cache_path = tempdir(),
  ref = "master",
  subdir = NULL,
  auth_token = github_pat(),
  host = "https://api.github.com"
)

```

Arguments

path	a local path to a posterior database. Defaults to ‘pdb_path’ option or PDB_PATH environment variable.
cache_path	The path to the pdb cache. Default is R temporary directory. This is used to store files locally and without affecting the database.

x	an object to access a pdb for, if character this is how to identify the pdb (path for local pdb, repo for github pdb)
...	further arguments for specific methods to setup a pdb.
pdb_type	Type of posterior database connection. Either local or github.
directory	the directory to look for the [.pdb_config.yml] file
repo	Repository address in the format 'username/repo[/subdir][@ref#pull]'. Alternatively, you can specify 'subdir' and/or 'ref' using the respective parameters (see below); if both is specified, the values in 'repo' take precedence.
ref	Desired git reference. Could be a commit, tag, or branch name. Defaults to "master".
subdir	subdirectory within repo that contains the posterior database.
auth_token	To use a private repo, generate a personal access token (PAT) in "https://github.com/settings/tokens" and supply to this argument. This is safer than using a password because you can easily delete a PAT without affecting any others. Defaults to the 'GITHUB_PAT' environment variable.
host	GitHub API host to use. Override with your GitHub enterprise hostname, for example, "github.hostname.com/api/v3".

Details

Connect to a posterior database locally or in a github repo.

[pdb_config()] read [.pdb_config.yml] in [directory] and use that to setup a pdb connection.

The connection [pdb_default()] first checks if there exists a [.pdb_config.yml] file in the working directory. If it exist, [pdb_config()] is used to setup, the connection. If no [.pdb_config.yml] file is found, [pdb_local()] is used to setup a pdb. If no local pdb is found, [pdb_github()] is used.

Value

a pdb object

pdb_stan_sampling_versions

Extract relevant stan versions

Description

Extract relevant stan versions

Usage

pdb_stan_sampling_versions()

pdb_version	<i>Get version of the pdb</i>
-------------	-------------------------------

Description

Get version of the pdb

Usage

```

pdb_version(pdb, ...)

## S3 method for class 'pdb_local'
pdb_version(pdb, ...)

## S3 method for class 'pdb_github'
pdb_version(pdb, ...)
```

Arguments

pdb	a pdb object to return version for.
...	Further argument to methods.

Value

the git sha for the posterior database.

posterior	<i>Access a posterior in the posterior database</i>
-----------	---

Description

Access a posterior in the posterior database

Usage

```

posterior(x, pdb = pdb_default(), ...)

as.posterior(x, pdb = pdb_default(), ...)

## S3 method for class 'character'
posterior(x, pdb = pdb_default(), ...)

## S3 method for class 'list'
as.posterior(x, pdb = pdb_default(), ...)
```



```

pdb_posterior(x, pdb = pdb_default(), ...)

as.pdb_posterior(x, pdb = pdb_default(), ...)

```

Arguments

x	a posterior name that exist in the posterior database or a list used to construct a posterior object.
pdb	a pdb posterior database object.
...	currently not in use.

Details

To setup a posterior object from a list, a minimum of a ‘pdb_model’, ‘pdb_data’, and a ‘dimension’ element need to be included. See ‘posterior("eight_schools")\$dimensions’ for an example.

posteriors_tbl_df	<i>Create Posterior Database tibbles</i>
-------------------	--

Description

Create Posterior Database tibbles

Usage

```
posteriors_tbl_df(pdb = pdb_default(), ...)
```

Arguments

pdb	a pdb object.
...	further arguments to supply to <code>dplyr::filter()</code>

Details

Generates a tibble data frame of all posteriors in the database and their side information

posterior_dimension_names

Construct dimension names from a posterior dimension list

Description

Construct dimension names from a posterior dimension list

Usage

```
posterior_dimension_names(x)
```

Arguments

x a dimensions slot from a [pdb_posterior]

posterior_names

Get all existing posterior names from a posterior database or posterior objects.

Description

Get all existing posterior names from a posterior database or posterior objects.

Usage

```
posterior_names(x = pdb_default(), ...)
```

```
posterior_name(x = pdb_default(), ...)
```

Arguments

x a pdb, pdb_model_code, pdb_data, posterior object or a list of posterior objects.

... further arguments supplied to specific methods (not in use)

Details

If a pdb_model_code or a pdb_data object is supplied, the function returns the name of all posteriors that uses the data or the model.

read_json_from_pdb	<i>Read JSON objects from the posterior database</i>
--------------------	--

Description

Read JSON objects from the posterior database

Usage

```
read_json_from_pdb(fn, path, pdb, ...)
```

Arguments

fn	file name
path	path to file name in pdb
pdb	a [pdb] object
...	further arguments supplied to [jsonlite::read_json()]

reference_posterior_draws_file_path	<i>Extract data for posterior</i>
-------------------------------------	-----------------------------------

Description

Extract data for posterior

Usage

```
reference_posterior_draws_file_path(x, ...)

## S3 method for class 'pdb_posterior'
reference_posterior_draws_file_path(x, ...)

## S3 method for class 'character'
reference_posterior_draws_file_path(x, pdb = pdb_default(), ...)

## S3 method for class 'pdb_reference_posterior_info'
reference_posterior_draws_file_path(x, pdb = pdb_default(), ...)
```

Arguments

x	an object to access file path to.
...	further arguments supplied to methods.
pdb	a pdb object.

reference_posterior_info

Reference posterior information

Description

Reference posterior information

Usage

```
reference_posterior_info(x, type, pdb = pdb_default(), ...)

as.reference_posterior_info(x, type, pdb = pdb_default(), ...)

pdb_reference_posterior_info(x, type, pdb = pdb_default(), ...)

as.pdb_reference_posterior_info(x, type, pdb = pdb_default(), ...)

reference_posterior_draws_info(x, pdb = pdb_default(), ...)

pdb_reference_posterior_draws_info(x, pdb = pdb_default(), ...)

## S3 method for class 'pdb_posterior'
reference_posterior_info(x, type, ...)

## S3 method for class 'character'
reference_posterior_info(x, type, pdb = pdb_default(), ...)

## S3 method for class 'list'
as.reference_posterior_info(x, type = NULL, pdb = NULL, ...)
```

Arguments

x	a posterior object to access the reference posterior for.
type	Type of reference posterior [draws] or [summary_statistic].
pdb	a pdb posterior database connection.
...	Currently not used.

Details

Reference posterior information on how, when and by whom the reference posterior was computed.

See Also

reference_posterior_draws

reference_posterior_names

Get all existing reference posterior names from a posterior database

Description

Get all existing reference posterior names from a posterior database

Usage

```
reference_posterior_names(pdb = pdb_default(), type, ...)
```

```
## S3 method for class 'pdb_local'
```

```
reference_posterior_names(pdb = pdb_default(), type, ...)
```

Arguments

pdb	a pdb object.
type	supported reference posterior types.
...	Further argument to methods.

reference_posterior_summary_statistic

Reference posterior summary statistics

Description

Reference posterior summary statistics

Usage

```
reference_posterior_summary_statistic(x, ...)
```

```
pdb_reference_posterior_summary_statistic(x, ...)
```

```
## S3 method for class 'character'
```

```
reference_posterior_summary_statistic(x, pdb = pdb_default(), type, ...)
```

```
## S3 method for class 'pdb_posterior'
```

```
reference_posterior_summary_statistic(x, type, ...)
```

```
## S3 method for class 'pdb_reference_posterior_info'
```

```
reference_posterior_summary_statistic(x, pdb = pdb_default(), type, ...)
```

```
## S3 method for class 'list'
reference_posterior_summary_statistic(x, info, type, ...)

reference_posterior_summary_statistics(x, ...)

pdb_reference_posterior_summary_statistics(x, ...)

## S3 method for class 'character'
reference_posterior_summary_statistics(x, pdb = pdb_default(), ...)

## S3 method for class 'pdb_posterior'
reference_posterior_summary_statistics(x, ...)
```

Arguments

x	a [posterior] object or a posterior name.
...	further arguments supplied to specific methods.
pdb	a [pdb] object (if [x] is a posterior name)
type	the type of summary statistic to extract
info	a [pdb_reference_posterior_info] object

Value

a [pdb_reference_posterior_summary_statistic] object.

remove_pdb	<i>Remove objects from local pdb</i>
------------	--------------------------------------

Description

a function to simplify removing object from a local pdb.

Usage

```
remove_pdb(x, pdb, ...)

## S3 method for class 'character'
remove_pdb(x, pdb, ...)

## S3 method for class 'pdb_data'
remove_pdb(x, pdb, remove_info = TRUE, ...)

## S3 method for class 'pdb_data_info'
remove_pdb(x, pdb, ...)

## S3 method for class 'pdb_model_code'
```

```

remove_pdb(x, pdb, remove_info = TRUE, ...)

## S3 method for class 'pdb_model_info'
remove_pdb(x, pdb, ...)

## S3 method for class 'pdb_posterior'
remove_pdb(x, pdb, ...)

## S3 method for class 'pdb_reference_posterior_draws'
remove_pdb(x, pdb, remove_info = TRUE, ...)

## S3 method for class 'pdb_reference_posterior_info'
remove_pdb(x, pdb, type, ...)

## S3 method for class 'pdb_reference_posterior_summary_statistic'
remove_pdb(x, pdb, remove_info = TRUE, ...)

```

Arguments

x	an object to remove to the pdb.
pdb	the pdb to remove from. Currently only a local pdb.
...	further arguments supplied to methods.
remove_info	should the information JSON be removed as well?
type	supported reference posterior types.

rename_pdb	<i>Rename a pdb object</i>
------------	----------------------------

Description

Rename a pdb object

Usage

```

rename_pdb(x, new_name, ...)

## S3 method for class 'pdb_data'
rename_pdb(x, new_name, ...)

## S3 method for class 'pdb_posterior'
rename_pdb(x, new_name, ...)

```

Arguments

x	an object to rename
new_name	the new name of the object
...	further arguments (not in use)

run_stan	<i>Run Stan on a posterior</i>
----------	--------------------------------

Description

Run Stan on a posterior

Usage

```
run_stan(x, stan_args, ...)

## S3 method for class 'pdb_posterior'
run_stan(x, stan_args, ...)
```

Arguments

x	a [pdb_posterior] object.
stan_args	Arguments supplied to [rstan::stan] to compute the posterior
...	currently not in use.

subset.pdb_reference_posterior_draws	<i>Subset a [pdb_reference_posterior_draws] object</i>
--------------------------------------	--

Description

Subset a [pdb_reference_posterior_draws] object

Usage

```
## S3 method for class 'pdb_reference_posterior_draws'
subset(x, variable, ...)
```

Arguments

x	a [pdb_reference_posterior_draws] to subest
variable	parameter names to subset.
...	Further arguments (not used).

summary_statistic_type

Extract the type of summary statistic

Description

Extract the type of summary statistic

Usage

```
summary_statistic_type(x)
```

Arguments

x a [pdb_reference_posterior_summary_statistic]

thin_draws.pdb_reference_posterior_draws

Thin draws to reduce their size and autocorrelation of the chains.

Description

Thin [pdb_reference_posterior_draws] objects to reduce their size and autocorrelation of the chains.

Usage

```
thin_draws.pdb_reference_posterior_draws(x, thin, ...)
```

Arguments

x An R object for which the methods are defined.
thin A positive integer specifying the period for selecting draws.
... Arguments passed to individual methods (if applicable).

Value

A thinned [pdb_reference_posterior_draws] object.

write_pdb

Write objects to pdb

Description

a function to simplify writing to a local pdb.

Usage

```
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_reference_posterior_info'
write_pdb(x, pdb, overwrite = FALSE, type, ...)

## S3 method for class 'pdb_reference_posterior_draws'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_reference_posterior_summary_statistic'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_data'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_data_info'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'stanmodel'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_model_code'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_model_info'
write_pdb(x, pdb, overwrite = FALSE, ...)

## S3 method for class 'pdb_posterior'
write_pdb(x, pdb, overwrite = FALSE, ...)
```

Arguments

x	an object to write to the pdb.
pdb	the pdb to write to. Currently only a local pdb.
overwrite	overwrite existing file?
...	further arguments supplied to methods.
type	supported reference posterior types.

Index

alias_names, 3
as.data.frame.pdb_posterior, 3
as.data.frame.pdb_posteriors
 (as.data.frame.pdb_posterior),
 3
as.data_info (data_info), 11
as.model_code (model_code), 16
as.model_info (data_info), 11
as.pdb_data (get_data), 14
as.pdb_data_info (data_info), 11
as.pdb_model_code (model_code), 16
as.pdb_model_info (data_info), 11
as.pdb_posterior (posterior), 24
as.pdb_reference_posterior_draws
 (as.reference_posterior_draws.stanfit),
 4
as.pdb_reference_posterior_info
 (reference_posterior_info), 28
as.posterior (posterior), 24
as.reference_posterior_draws
 (as.reference_posterior_draws.stanfit),
 4
as.reference_posterior_draws.stanfit,
 4
as.reference_posterior_info
 (reference_posterior_info), 28
as.stan_code (model_code), 16
assert_checked_reference_posterior_draws,
 5
assert_checked_summary_statistics_draws
 (assert_checked_reference_posterior_draws),
 5
assert_reference_posterior_draws
 (as.reference_posterior_draws.stanfit),
 4

bibliography, 6

check_pdb, 6
check_pdb_aliases (check_pdb), 6
check_pdb_all_data_have_posterior
 (check_pdb), 6
check_pdb_all_models_have_posterior
 (check_pdb), 6
check_pdb_all_reference_posteriors_have_posterior
 (check_pdb), 6
check_pdb_posterior, 7
check_pdb_posterior_references
 (check_pdb), 6
check_pdb_posterior_run_stan
 (check_pdb), 6
check_pdb_read_data (check_pdb), 6
check_pdb_read_model_code (check_pdb), 6
check_pdb_read_reference_posterior_draws
 (check_pdb), 6
check_pdb_references (check_pdb), 6
check_reference_posterior_draws, 8
check_summary_statistics_draws, 9
compute_reference_posterior_draws, 9
compute_reference_posterior_draws_stan_sampling,
 10
compute_reference_posterior_summary_statistic,
 10
compute_summary_statistic
 (compute_reference_posterior_summary_statistic),
 10

data_file_path, 11
data_info, 11
data_names, 12
filter_posteriors, 13
framework, 13
framework<- (framework), 13
get_data, 14
github_pat, 15

handle_aliases, 15

info, 15

[info<-](#), [16](#)
[model_code](#), [16](#)
[model_code_file_path](#) ([model_code](#)), [16](#)
[model_info](#) ([data_info](#)), [11](#)
[model_names](#), [17](#)
[model_names.pdb_github](#) ([data_names](#)), [12](#)

[pdb](#) ([pdb_local](#)), [22](#)
[pdb<-](#), [18](#)
[pdb_aliases](#), [18](#)
[pdb_assert_file_exist](#), [19](#)
[pdb_bibliography](#) ([bibliography](#)), [6](#)
[pdb_cache_path](#), [20](#)
[pdb_cache_rm](#), [20](#)
[pdb_cached_local_file_path](#), [19](#)
[pdb_compare_stan_models](#), [21](#)
[pdb_config](#) ([pdb_local](#)), [22](#)
[pdb_data](#) ([get_data](#)), [14](#)
[pdb_data_info](#) ([data_info](#)), [11](#)
[pdb_default](#) ([pdb_local](#)), [22](#)
[pdb_file_copy](#), [21](#)
[pdb_github](#) ([pdb_local](#)), [22](#)
[pdb_local](#), [22](#)
[pdb_model_code](#) ([model_code](#)), [16](#)
[pdb_model_info](#) ([data_info](#)), [11](#)
[pdb_posterior](#) ([posterior](#)), [24](#)
[pdb_reference_posterior_draws](#)
 ([as.reference_posterior_draws.stanfit](#)), [4](#)
[pdb_reference_posterior_draws_info](#)
 ([reference_posterior_info](#)), [28](#)
[pdb_reference_posterior_info](#)
 ([reference_posterior_info](#)), [28](#)
[pdb_reference_posterior_summary_statistic](#)
 ([reference_posterior_summary_statistic](#)), [29](#)
[pdb_reference_posterior_summary_statistics](#)
 ([reference_posterior_summary_statistic](#)), [29](#)

[pdb_stan_code](#) ([model_code](#)), [16](#)
[pdb_stan_sampling_versions](#), [23](#)
[pdb_version](#), [24](#)
[posterior](#), [24](#)
[posterior_dimension_names](#), [26](#)
[posterior_name](#) ([posterior_names](#)), [26](#)
[posterior_names](#), [26](#)
[posteriors_tbl_df](#), [25](#)

[read_json_from_pdb](#), [27](#)
[reference_posterior_draws](#)
 ([as.reference_posterior_draws.stanfit](#)), [4](#)
[reference_posterior_draws_file_path](#), [27](#)
[reference_posterior_draws_info](#)
 ([reference_posterior_info](#)), [28](#)
[reference_posterior_info](#), [28](#)
[reference_posterior_names](#), [29](#)
[reference_posterior_names.pdb_github](#)
 ([data_names](#)), [12](#)
[reference_posterior_summary_statistic](#), [29](#)
[reference_posterior_summary_statistics](#)
 ([reference_posterior_summary_statistic](#)), [29](#)

[remove_pdb](#), [30](#)
[rename_pdb](#), [31](#)
[run_stan](#), [32](#)

[stan_code](#) ([model_code](#)), [16](#)
[stan_code_file_path](#) ([model_code](#)), [16](#)
[stan_data](#) ([data_file_path](#)), [11](#)
[stan_data_file_path](#) ([data_file_path](#)), [11](#)
[subset.pdb_reference_posterior_draws](#), [32](#)
[summary_statistic_type](#), [33](#)

[thin_draws.pdb_reference_posterior_draws](#), [33](#)

[write_pdb](#), [34](#)